


Floordrain for ACO ShowerDrain S+

Product information

ACO Product benefits

- Preassembled sealing membrane
- Corresponding according W3-I according to German Standard DIN 18534
- Compliant with noise protection DIN 4109 and VDI 4100



- Made of plastic
- Product class A (DIN EN 1253-1)
- Drain socket suitable for all push fit pipe socket systems
- Socket type: ND 50, inclination 1,5°
- Foul air trap: 2-part, removeable
- With pre-assembled sealing membrane
 - ☐ For optimum connection of a compound sealing
 - ☐ 60 mm overlap
 - ☐ Corresponding acc. tensile test of EN 1253-1
- With secondary drainage
- With mounting set and protective cover
- Assembly: Modular system consisting of shower channel profile and floor drain

Flowrate depending on grating and floor drain:



Design Stripes:

- Floor drain S+ with water trap 50 mm (DIN EN 1253-1)
 - ☐ 0,8 l/s with 20 mm build up
 - ☐ 0,7 l/s with 10 mm build up
- Floor drain S+ with water trap 30 mm
 - ☐ 0,6 l/s with 20 mm build up
 - ☐ 0,4 l/s with 10 mm build up



Design Plate:

- Floor drain S+ with water trap 50 mm (DIN EN 1253-1)
 - ☐ 0,6 l/s with 20 mm build up
 - ☐ 0,5 l/s with 10 mm build up
- Floor drain S+ with water trap 30 mm
 - ☐ 0,5 l/s with 20 mm build up
 - ☐ 0,4 l/s with 10 mm build up

Item Technical Data 9010.51.21

	Nominal width	Socket inclination	Installed height	Water trap depth
 	DN 50	1,5°	70 – 160 mm	Water trap depth: 30 mm

Accessories

Description	Used with	Item number
Odour trap <ul style="list-style-type: none">■ ACO ShowerDrain S + odour trap<ul style="list-style-type: none">□ Replacement odor trap□ Two-part and removable□ Made of plastic	<ul style="list-style-type: none">■ ACO ShowerDrain S +<ul style="list-style-type: none">□ Floordrain	
 With water trap 50 mm		9010.51.27
 With water trap 30 mm		9010.51.28

You can find further accessories under → <https://www.buildingdrainage.aco/search/?q=9010.51.21>